

DOSE RATE MEASURING SYSTEM

GRAETZ X5C plus SE

for personal radiation protection

Product features

- ◆ Dose rate meter for the measurement of gamma radiation and X-rays for ambient dose rate equivalent $H^*(10)$
- ◆ Detector: energy compensated GM tube
- ◆ Large digital indication of measured values on LC display; illuminable and with colored (red) warning function
- ◆ Selectable dose rate or dose indication with integration time
- ◆ Additional quasi-analogue indication of dose rate (3.5 decades, logarithmic bargraph)
- ◆ Indication of peak and average dose rate value
- ◆ Four free programmable dose and dose rate alarm thresholds
- ◆ Automatic or manual storage of measured dose rate values together with date and time
- ◆ Evaluation/indication of residual time for staying in the current radiation field with regard to the maximum allowed dose
- ◆ Switchable acoustic single-pulse indication
- ◆ Clear menu-driven user navigation for easy operation, partly secured by password
- ◆ Storage of set parameters even when the device is switched off or during battery change
- ◆ Continuous self-testing and monitoring ensure high reliability
- ◆ Compact metallised housing made of high impact-proof plastic, easy to decontaminate, protection class IP67
- ◆ RS-232 interface, enables configuration of the device and readout of stored measured values with the optionally available PC cable and the 'X5C software tool'.
- ◆ Basic unit can be combined either directly or by probe cable with various probes (see separate leaflet):
 - for extending the measuring range up to 10 Sv/h
 - for detecting α -, β - and γ -radiation
 - for measuring in liquids
 - for measurements at „hard-to-get-to“ places
 - Telescope Probe DE for measurements from a safe distance
 - Scintillation probe 2002 for measuring low dose rates



Technical Data

| | |
|---|--|
| Dose rate indication range: | 0 nSv/h – 19.99 mSv/h |
| Dose rate range: | 1 μSv/h – 19.99 mSv/h |
| Dose indication range: | 0.01 nSv – 10 Sv |
| Dose measuring range: | 0.5 μSv – 10 Sv |
| Energy range: | 40 keV – 1.3 MeV |
| Dose rate alarm thresholds: | 4 (standard: 7.5 μSv/h, 25 μSv/h, 40 μSv/h, 300 μSv/h), free programmable in the range 1 μSv/h – 19.99 mSv/h |
| Dose alarm thresholds: | 4 (standard: 200 μSv, 500 μSv, 1000 μSv, 2 mSv), free programmable in the range 1 μSv – 10 Sv |
| Temperature range: | -30°C up to +60°C |
| Dimensions: | 152 x 82 x 39 mm |
| Weight: | approx. 385 g |
| Power supply: | 9V battery |
| Acoustic alarm: | 65 dB(A) measured in 30 cm distance |
| According to German Fire Brigades Approval No.: | DL/FW/IdF 080221/1 |